

CENTERFIRE PISTOL & REVOLVER AMMUNITION BALLISTICS



Golden Saber™

Core-Lokt® Hunting

Disintegrator™ Frangible

Caliber	Order No.	Primer No.	Weight (grs.)	Bullet Style	Velocity (ft./sec.)			Energy (ft.-lbs.)			Mid-range Trajectory		
					Muzzle	50 yds.	100 yds.	Muzzle	50 yds.	100 yds.	50 yds.	100 yds.	B.L.
25 (6.35mm) Auto. Pistol	R25AP	1 1/2	50	Metal Case	760	707	659	64	56	48	2.0"	8.7"	2"
.32 S&W	R32SW	1 1/2	88	Lead	680	645	610	90	81	73	2.5"	10.5"	3"
.32 S&W Long	R32SWL	1 1/2	98	Lead	705	670	635	115	98	88	2.3"	10.5"	4"
.32 (7.65mm) Auto. Pistol	R32AP	1 1/2	71	Metal Case	905	855	810	129	115	97	1.4"	5.8"	4"
.357 Mag. (Vented Barrel Ballistics)	R357M7	5 1/2	110	Semi-Jacketed Hollow Point	1295	1094	975	410	292	232	0.8"	3.5"	4"
	R357M1	5 1/2	125	Semi-Jacketed Hollow Point	1450	1240	1090	583	427	330	0.6"	2.8"	4"
	GS357MA	5 1/2	125	Brass-Jacketed Hollow Point	1220	1095	1009	413	333	283	0.8"	3.5"	4"
	RH357MA	5 1/2	165	JHP Core-Lokt®	1290	1189	1108	610	518	450	0.7"	3.1"	8 1/8"
	R357M2	5 1/2	158	Semi-Jacketed Hollow Point	1235	1104	1015	535	428	361	0.8"	3.5"	4"
	R357M3	5 1/2	158	Soft Point	1235	1104	1015	535	428	361	0.8"	3.5"	4"
	R357M5	5 1/2	158	Semi-Wadcutter	1235	1104	1015	535	428	361	0.8"	3.5"	4"
	R357M10	5 1/2	180	Semi-Jacketed Hollow Point	1145	1053	985	524	443	388	0.9"	3.9"	8 1/8"
9mm Luger Auto. Pistol	R9MM1	1 1/2	115	Jacketed Hollow Point	1155	1047	971	341	280	241	0.9"	3.9"	4"
	R9MM10	1 1/2	124	Jacketed Hollow Point	1120	1028	960	346	291	254	1.0"	4.1"	4"
	R9MM2	1 1/2	124	Metal Case	1110	1030	971	339	292	259	1.0"	4.1"	4"
	R9MM3	1 1/2	115	Metal Case	1135	1041	973	329	277	242	0.9"	4.0"	4"
	R9MM6	1 1/2	115	Jacketed Hollow Point (+P)†	1250	1113	1019	399	316	265	0.8"	3.5"	4"
	R9MM8	1 1/2	147	Jacketed Hollow Point (Subsonic)	990	941	900	320	289	264	1.1"	4.9"	4"
	LF9MMA	1 1/2	101	Disintegrator™ Plated Frangible	1220	1092	1004	334	267	226	0.9"	3.6"	4"
	GS9MMB	1 1/2	124	Brass-Jacketed Hollow Point	1125	1031	963	349	293	255	1.0"	4.0"	4"
	GS9MMC	1 1/2	147	Brass-Jacketed Hollow Point	990	941	900	320	289	264	1.1"	4.9"	4"
	GS9MMD	1 1/2	124	Brass-Jacketed Hollow Point (+P)†	1180	1089	1021	384	327	287	0.8"	3.8"	4"
.380 Auto. Pistol	R380AP	1 1/2	95	Metal Case	955	865	785	190	160	130	1.4"	5.9"	4"
	R380A1	1 1/2	88	Jacketed Hollow Point	990	920	868	191	165	146	1.2"	5.1"	4"
	GS380B	1 1/2	102	Brass-Jacketed Hollow Point	940	901	866	200	184	170	1.2"	5.1"	4"
.38 S&W	R38SW	1 1/2	146	Lead	685	650	620	150	135	125	2.4"	10.0"	4"
.38 Special (Vented Barrel Ballistics)	★ LF38SA	1 1/2	101	Lead-Free Frangible (+P)†	950	896	850	202	180	162	1.2"	5.3"	4"
	R38S10	1 1/2	110	Semi-Jacketed Hollow Point (+P)†	995	926	871	242	210	185	1.2"	5.1"	4"
	R38S16	1 1/2	110	Semi-Jacketed Hollow Point	950	890	840	220	194	172	1.4"	5.4"	4"
	R38S2	1 1/2	125	Semi-Jacketed Hollow Point (+P)†	945	898	858	248	224	204	1.3"	5.4"	4"
	GS38SB	1 1/2	125	Brass-Jacketed Hollow Point (+P)†	975	929	885	264	238	218	1.0"	5.2"	4"
	R38S3	1 1/2	148	Targetmaster® Lead WC Match	710	634	566	166	132	105	2.4"	10.8"	4"
	R38S5	1 1/2	158	Lead (Round Nose)	755	723	692	200	183	168	2.0"	8.3"	4"
	R38S14	1 1/2	158	Semi-Wadcutter (+P)†	890	855	823	278	257	238	1.4"	6.0"	4"
	R38S6	1 1/2	158	Semi-Wadcutter	755	723	692	200	183	168	2.0"	8.3"	4"
	R38S12	1 1/2	158	Lead Hollow Point (+P)†	890	855	823	278	257	238	1.4"	6.0"	4"
.38 Short Colt	R38SC	1 1/2	125	Lead	730	685	645	150	130	115	2.2"	9.4"	6"
.357 Sig.	R357S1	5 1/2	125	Jacketed Hollow Point	1350	1157	1032	506	372	296	0.7"	3.2"	4"
	★ LF357SA	5 1/2	104	Lead-Free Frangible	1400	1223	1094	453	345	276	0.6"	2.9"	4"
.40 S&W	R40SW1	5 1/2	155	Jacketed Hollow Point	1205	1095	1017	499	413	356	0.8"	3.6"	4"
	R40SW2	5 1/2	180	Jacketed Hollow Point	1015	960	914	412	368	334	1.3"	4.5"	4"
	LF40SWA	5 1/2	141	Disintegrator™ Plated Frangible	1135	1056	996	403	349	311	0.9"	3.9"	4"
	GS40SWA	5 1/2	165	Brass-Jacketed Hollow Point	1150	1040	964	485	396	340	1.0"	4.0"	4"
	GS40SWB	5 1/2	180	Brass-Jacketed Hollow Point	1015	960	914	412	368	334	1.3"	4.5"	4"
.41 Rem. Mag. (Vented BBL Ballistics)	R41MG1	2 1/2	210	Soft Point	1300	1162	1062	788	630	526	0.7"	3.2"	4"
.44 Rem. Mag. (Vented BBL Ballistics)	R44MG5	2 1/2	180	Semi-Jacketed Hollow Point	1610	1365	1175	1036	745	551	0.5"	2.3"	4"
	R44MG2	2 1/2	240	Soft Point	1180	1081	1010	741	623	543	0.9"	3.7"	4"
	R44MG3	2 1/2	240	Semi-Jacketed Hollow Point	1180	1081	1010	741	623	543	0.9"	3.7"	4"
	RH44MGA	2 1/2	275	JHP Core-Lokt®	1235	1142	1070	931	797	699	0.8"	3.3"	6 1/2"
.44 S&W Special	R44SW	2 1/2	246	Lead	755	725	695	310	285	265	2.0"	8.3"	6"
.45 Colt	R45C	2 1/2	250	Lead	860	820	780	410	375	340	1.6"	6.6"	5"
	R45C1	2 1/2	225	Semi-Wadcutter	960	890	832	460	395	346	1.3"	5.5"	5"
.45 Auto.	R45AP2	2 1/2	185	Jacketed Hollow Point	1000	939	889	411	362	324	1.1"	4.9"	5"
	R45AP4	2 1/2	230	Metal Case	835	800	767	356	326	300	1.6"	6.8"	5"
	R45AP7	2 1/2	230	Jacketed Hollow Point (Subsonic)	835	800	767	356	326	300	1.6"	6.8"	5"
	LF45APA	2 1/2	175	Disintegrator™ Plated Frangible	1020	923	851	404	331	281	1.2"	5.1"	5"
	GS45APA	2 1/2	185	Brass-Jacketed Hollow Point	1015	951	899	423	372	332	1.1"	4.5"	5"
	GS45APB	2 1/2	230	Brass-Jacketed Hollow Point	875	833	795	391	355	323	1.5"	6.1"	5"
	GS45APC	2 1/2	185	Brass-Jacketed Hollow Point (+P)†	1140	1042	971	534	446	388	1.0"	4.0"	5"

†Ammunition with (+P) on the case headstamp is loaded to higher pressure. Use only in firearms designated for this cartridge and so recommended by the gun manufacturer.

★ New For 2001